

# FF511LBIPLUSADA



32.5" x 19.25" x 21.38" (H x W x D)

ADA compliant 20" wide built-in undercounter all-refrigerator, auto defrost with an internal fan, thermometer, and lock

**Highlights:**

- 32" height fits under lower ADA compliant counters
- Flexible design allows built-in or freestanding use in 20" wide spaces
- Factory installed lock provides security you can count on

**Product Features:**

ADA compliant	32" high to fit under lower ADA compliant counters
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Built-in capable	Make the best use of space by installing your appliance under the counter
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Thermometer	Thermometer provides external readout of current and high/low temperatures
Internal fan with heat sink	Fan-forced cooling helps the unit stay evenly cooled from top to bottom
Factory installed lock	Top-mounted for convenient security
Fully finished white cabinet	Allows the unit to be used freestanding
Automatic defrost	Reduced maintenance with auto defrost system

## FF511LBIPLUSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.5" (83 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with Handle	23.0" (58 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Shipping Weight	85.0 lbs. (39 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101039961
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	1.75oz.
High Side PSI	205.0
Low Side PSI	103.0
Level Legs Qty	2
Interior Light	Yes
Dimensions	
Interior Height	28.5" (72 cm)
Interior Width	15.75" (40 cm)
Interior Depth	18.0" (46 cm)

Compressor Step Height	8.0" (20 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.75" (17 cm)

