

FF7BCSS



33.25" x 23.75" x 23.5" (H x W x D)

Commercially listed built-in undercounter all-refrigerator for general purpose use with stainless steel exterior, towel bar handle, and automatic defrost

Highlights:

Commercially approved for use in foodservice establishments

Complete stainless steel construction adds luxury to any setting

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces	
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets	
Fully finished cabinet	Allows the refrigerator to be used freestanding	
Complete stainless steel construction	Durable design with lasting elegance	
Professional towel bar handle	Curved handle in brushed stainless steel offers a sturdy grip with professional elegance	
Automatic defrost	Reduced user maintenance with automatic defrost	
Adjustable glass shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up	
One piece interior liner	Enjoy easy clean-up with a seamless liner that won't hold a mess in hidden crevices	





FF7BCSS Specifications:

Height of Cabinet 32.63" (83 cm Height to Hinge Cap 33.25" (84 cm Width 23.75" (60 cm Depth 23.5" (60 cm Depth with Handle 25.25" (64 cm Depth with door at 90° 45.5" (116 cm Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Stee US Electrical Safety ULC		
Width 23.75" (60 cm Depth 23.5" (60 cm Depth with Handle 25.25" (64 cm Depth with door at 90° 45.5" (116 cm Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Depth 23.5" (60 cm Depth with Handle 25.25" (64 cm Depth with door at 90° 45.5" (116 cm Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Steel US Electrical Safety UI		
Depth with Handle 25.25" (64 cm Depth with door at 90° 45.5" (116 cm Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Depth with door at 90° 45.5" (116 cm Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Capacity 5.5 cu.ft. (156 L Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Defrost Type Automatic Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Door Stainless Stee Cabinet Stainless Stee US Electrical Safety UI		
Cabinet Stainless Stee US Electrical Safety UI		
US Electrical Safety UI		
<u> </u>		
Canadian Electrical		
Canadian Electrical ULC Safety		
Sanitation ETL-S		
Amps 1.3		
Voltage/Frequency 115 V AC/60 Hz		
Weight 100.0 lbs. (45 kg		
Shipping Weight 105.0 lbs. (48 kg		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Years		
UPC 761101013466		
Refrigerator Features		
Door Swing RHE		
Reversible Factory Reversible		
Height Adjustable		
Shelf Type Glass		
Shelf Qty		
Adjustable Shelves Yes		
Thermostat Type Dia		
Fan Type Exterio		
Refrigerant Type R134a		
Refrigerant Type R134a Refrigerant Amount 1.8oz		
Refrigerant Amount 1.8oz		
Refrigerant Amount 1.8oz High Side PSI 285.0		
Refrigerant Amount 1.8oz High Side PSI 285.0 Low Side PSI 70.0		
Refrigerant Amount 1.8oz High Side PSI 285.0 Low Side PSI 70.0 Level Legs Qty 4		

Interior Width	20.0" (51 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	6.0" (15 cm)



