accucold

ALF620LBISSHV



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in medical all-freezer capable of -25° C operation with lock, stainless steel wrapped door and thin handle

Highlights:

32 inch height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use

Factory installed lock provides security you can count on

Product Features:

| ADA Compliant | 32 inch height is designed to fit under ADA compliant counters | |
|-------------------------------------|--|--|
| Slim undercounter dimensions | Less than 24 inches wide to fit tight spaces | |
| Built-in capable | Make the best use of space by installing your appliance under the counter and flush with other cabinetry | |
| Fully finished white cabinet | Allows the unit to be used freestanding | |
| Factory installed lock | Keep contents secure with a front lock on the door | |
| Stainless steel door | 304 grade stainless steel wrapped door for lasting durability | |
| Professional stainless steel handle | Thin 14mm diameter on stainless steel handle, mounted vertically for a sleek look | |
| -25° capable | Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials | |
| Three slide-out drawers | Conveniently organize your items while keeping the temperature stable when the door is opened | |

 \checkmark



accuceld

ALF620LBISSHV Specifications:

| Height of Cabinet | 32.0" (81 cm) |
|---|--|
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.63" (60 cm) |
| Depth | 23.5" (60 cm) |
| Depth with Handle | 24.25" (62 cm) |
| Depth with door at 90° | 45.0" (114 cm) |
| Capacity | 3.2 cu.ft. (91 L) |
| Defrost Type | Manual |
| Door | Stainless Steel |
| Cabinet | White |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 95.0 lbs. (43 kg) |
| Shipping Weight | 98.0 lbs. (44 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101004570 |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Interior Height | 24.25" (62 cm) |
| La (a n' a n) A/l al (| |
| Interior Width | 17.75" (45 cm) |
| Interior Width Interior Depth | 17.75" (45 cm) 16.5" (42 cm) |
| | |
| Interior Depth | 16.5" (42 cm) |
| Interior Depth Thermostat Type | 16.5" (42 cm) Digital |
| Interior Depth Thermostat Type Fan Type | 16.5" (42 cm) Digital Exterior |
| Interior Depth Thermostat Type Fan Type Refrigerant Type | 16.5" (42 cm) Digital Exterior R134a |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. 235.0 |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. 235.0 70.0 |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. 235.0 70.0 4 |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Interior Drawers | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. 235.0 70.0 4 Yes |
| Interior Depth Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Interior Drawers Drawers Qty | 16.5" (42 cm) Digital Exterior R134a 2.7 oz. 235.0 70.0 4 Yes 3 |

Temperature Range



