

FFAR22LW7CSSMED



20.5" x 17.38" x 19" (H x W x D)

Commercially listed compact auto defrost all-refrigerator in stainless steel with a lock, temperature alarm, internal fan, and hospital grade cord

Highlights:

Medical grade design conforms with CDC guidelines for vaccine storage

Compact size is ideal for countertop use

Commercially listed to NSF-7 standards

Product Features:

Compact dimensions	Ideal size for use on top of counters
Commercially listed	CSA-S listed to NSF-7 standards
Automatic defrost	Reduced maintenance with auto defrost system
Stainless steel exterior	Fully wrapped in 304 grade stainless steel
Flat door liner	Interior design meets CDC guidelines for sensitive storage
Internal fan with heat sink	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Removable shelf	Wired shelf provided

FFAR22LW7CSSMED Specifications:

Overview	
Height of Cabinet	20.13" (51 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.0" (48 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	CSA
Canadian Electrical Safety	CSA
Sanitation	CSA-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	35.0 lbs. (16 kg)
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101040936
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	1.94oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs Qty	2
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	14.18" (36 cm)
Interior Depth	14.5" (37 cm)
Compressor Step Height	6.75" (17 cm)
Compressor Step Width	14.18" (36 cm)
Compressor Step Depth	5.25" (13 cm)

