

# FS20LGL7CSSVK



20" x 19.75" x 21" (H x W x D)

DISCONTINUED: Replaced by SCFU386VKCSS

### Highlights:

Commercially approved for use in foodservice establishments

Factory-installed lock provides security you can count on

Glass door highlights collection

### Product Features:

Commercially approved	ETL-S Approved to ANSI-NSF Standard 7 and CalCode Compliant
Compact dimensions	Square footprint for placement on top of counters
Fully wrapped stainless steel cabinet	Allows the unit to be used freestanding
Glass door	Display your collection with unique style
5°F Operation	Designed to cool vodka at the ideal temperature for service
Ceiling racks	Hang martini glasses for a luxurious look
Front-mounted lock	Keep contents secure with a key lock on the door
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system
Fluorescent lighting	Illuminate your collection by switching on the interior light



## FS20LGL7CSSVK Specifications:

Overview	
Height of Cabinet	20.75" (53 cm)
Height to Hinge Cap	20.0" (51 cm)
Width	19.75" (50 cm)
Depth	21.0" (53 cm)
Depth with Handle	20.0" (51 cm)
Depth with door at 90°	38.0" (97 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Glass
Cabinet	Stainless Steel
US Electrical Safety	UL
Sanitation	NSF
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	68.0 lbs. (31 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101022222
Freezer	
Door Swing	RHD
Reversible	No
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Interior Light	Yes
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

