



SCR1155



57" x 23.63" x 22.25" (H x W x D)

DISCONTINUED: Replaced by the SCR1156

Highlights:

- Double pane tempered glass door features stainless steel handle trim and pro handle
- Commercially listed to NSF-7 standards for use in foodservice establishments
- Factory installed lock provides security you can count on

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
Factory installed lock	Keyed lock for secure interior
Double pane tempered glass door	Heat-safe glass door offers full display all the way down to the floor
Recessed LED lighting	Energy efficient lighting offers full view of interior
Digital thermostat	Electronic controls for precise temperature management with a readout in Celsius or Fahrenheit; temperature range: 34-43 °F
Reversible door	User reversible door swing
Professional handle	Solid chrome handle with brushed stainless steel look
Adjustable wire shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup

SCR1155 Specifications:

Overview	
Height of Cabinet	57.0" (145 cm)
Width	23.63" (60 cm)
Depth	22.25" (57 cm)
Depth with Handle	24.13" (61 cm)
Depth with door at 90°	44.5" (113 cm)
Capacity	11.0 cu.ft. (311 L)
Defrost Type	Frost-Free
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	2.8
Voltage/Frequency	115 V AC/60 Hz
Weight	153.0 lbs. (69 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101001197

Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	3.88oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs Qty	4
Interior Light	Yes

Dimensions	
Interior Height	48.25" (123 cm)
Interior Width	19.5" (50 cm)
Interior Depth	17.38" (44 cm)
Compressor Step Height	5.5" (14 cm)

Compressor Step Width	19.5" (50 cm)
Compressor Step Depth	5.0" (13 cm)

