# SÜN

## SCR600BLPUBCSS



#### 34.5" x 23.75" x 23.5" (H x W x D)

Commercially approved built-in undercounter craft beer Pub Cellar with digital thermostat, glass door, and stainless steel wrapped cabinet

#### **Highlights:**

UNAVAILABLE AT THIS TIME

Commercially approved for use in food service establishments

Perfect for storing or aging craft beer for long-term use

### **Product Features:**

Designed for craft beer storage	Wide range temperature control lets you manage the interior between 41° and 65°F for optimum storage of all types of beer	
Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry	
Digital thermostat	Exterior thermostat located in kickplate lets you manage the temperature without opening the door	
Double pane tempered glass door	Heat resistant design provides clear view of stored products, with an elegant trim in brushed aluminum	
Wrapped stainless steel cabinet	Elegant finish that allows the unit to function freestanding	
Professional towel bar handle	A curved handle in brushed stainless steel provides generous room for a comfortable grip	
Factory installed lock	Keyed lock for a secure interior	
Automatic defrost	Reduced user maintenance with automatic defrost	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

 $\checkmark$ 





### SCR600BLPUBCSS Specifications:

Height of Cabinet33.25" (84 cmHeight to Hinge Cap34.5" (88 cmWidth23.75" (60 cmDepth23.5" (60 cmDepth with Handle25.5" (65 cmDepth with door at 90°46.0" (117 cmCapacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULSanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kgParts & Labor Warranty1 Yea		
Width23.75" (60 cmDepth23.5" (60 cmDepth with Handle25.5" (65 cmDepth with door at 90°46.0" (117 cmCapacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULSanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HaShipping Weight161.0 lbs. (73 kg		
Depth23.5" (60 cmDepth with Handle25.5" (65 cmDepth with door at 90°46.0" (117 cmCapacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULCanadian ElectricalULCSanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
Depth with Handle25.5" (65 cmDepth with door at 90°46.0" (117 cmCapacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULCanadian ElectricalULCSafety1.0Voltage/Frequency115 V AC/60 HaShipping Weight161.0 lbs. (73 kg		
Depth with door at 90°46.0" (117 cmCapacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULCanadian ElectricalULCSafety1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
Capacity5.5 cu.ft. (156 LDefrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULCanadian ElectricalULCSafetySafetySanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HShipping Weight161.0 lbs. (73 kg		
Defrost TypeAutomaticDoorGlassCabinetStainless SteeUS Electrical SafetyULCanadian ElectricalULCSafetySaintationSanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
DoorGlassCabinetStainless SteeUS Electrical SafetyUICanadian ElectricalULCSafetySafetySanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
CabinetStainless SteeUS Electrical SafetyUICanadian ElectricalULCSafetySafetySanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
US Electrical Safety UI Canadian Electrical ULC Safety Sanitation ETL-S Amps 1.0 Voltage/Frequency 115 V AC/60 H2 Shipping Weight 161.0 lbs. (73 kg		
Canadian ElectricalULCSafetyETL-SSanitationETL-SAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
SafetySanitationAmps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
Amps1.0Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
Voltage/Frequency115 V AC/60 HzShipping Weight161.0 lbs. (73 kg		
Shipping Weight 161.0 lbs. (73 kg		
Parts & Labor Warranty 1 Yea		
Compressor Warranty 5 Years		
UPC 761101042190		
Wine Cellar		
Number of Zones		
Door Swing RHE		
Reversible Factory Reversible		
Adjustable Shelves Yes		
Shelf Type Glass		
Shelf Qty 4		
Thermostat Type Digita		
Interior Light		
Interior Light Yes		
Fan Type Exterio		
Fan Type Exterio		
Fan TypeExterioRefrigerant TypeR134a		
Fan TypeExterioRefrigerant TypeR134aRefrigerant Amount1.8 oz		
Fan TypeExterioRefrigerant TypeR134aRefrigerant Amount1.8 ozHigh Side PSI285.0		
Fan TypeExterioRefrigerant TypeR134aRefrigerant Amount1.8 ozHigh Side PSI285.0Low Side PSI70.0		
Fan TypeExterioRefrigerant TypeR134aRefrigerant Amount1.8 ozHigh Side PSI285.0Low Side PSI70.0Interior Height 126.0" (66 cm		

Compressor Step Width	20.75" (53 cm)
Compressor Step Depth	5.0" (13 cm)
Level Legs	4
Temperature Range	41 to 65°F



