

SWC525L7CSSADA



32.5" x 19.38" x 22.25" (H x W x D)

Commercially listed ADA compliant 20" wide wine cellar for built-in use, with stainless steel cabinet, lock and digital thermostat

Highlights:

32" height fits under lower ADA compliant counters

ETL-S listed for commercial use

Flexible design allows built-in or freestanding use in 20" wide spaces

Product Features:

| | |
|-------------------------------|---|
| ADA compliant | 32" high meets ADA guidelines |
| Commercially listed | ETL-S listed to NSF standards for commercial use |
| Slim 20" width | Full 4.5 cu.ft. capacity inside conveniently slim footprint |
| Built-in capable | Make the best use of space by installing your appliance under the counter |
| Fully finished cabinet | Allows the unit to be used freestanding |
| Stainless steel cabinet | Durable 304 grade wrapping |
| Professional towel bar handle | A curved stainless steel handle provides generous room for a comfortable grip |
| Factory installed lock | Keyed lock for secure interior |
| Automatic defrost | Reduced maintenance with auto defrost system |

SWC525L7CSSADA Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.5" (83 cm) |
| Width | 19.38" (49 cm) |
| Depth | 22.25" (57 cm) |
| Capacity | 4.5 cu.ft. (127 L) |
| Bottles | 40 bottles |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.5 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 67.0 lbs. (30 kg) |
| Shipping Weight | 70.0 lbs. (32 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101042640 |
| Wine Cellar | |
| Number of Zones | 1 |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Adjustable Shelves | Yes |
| Shelf Type | Scalloped |
| Shelf Qty | 6 |
| Thermostat Type | Digital |
| Interior Light | Yes |
| Refrigerant Type | R134a |
| Refrigerant Amount | 1.59 oz. |
| High Side PSI | 218.0 |
| Low Side PSI | 105.0 |
| Temperature Range | 45° to 65°F |

