

# VT175



33.25" x 66.75" x 28.63" (H x W x D)

Laboratory chest freezer capable of -30° C (-22° F) operation

### Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Chest freezer with generous 18 cu.ft. storage capacity

Factory installed lock provides security you can count on

### Product Features:

Commercially approved	UL-S listed to NSF-7 commercial standards and meets UL commercial standard 471
Large capacity	18 cu.ft. of storage space inside
-30° C (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Digital thermostat	Electronic controls for precise temperature management
Alarm with temperature display	Audible alarm sounds to warn of temperature variations with a digital readout of the interior temperature
Factory installed lock	Keep contents secure with a lock on the lid
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system
Corner protectors	Edges are protected from dents
100% CFC free	Environmentally friendly design does not contain ozone-damaging chemicals

## VT175 Specifications:

Overview	
Height of Cabinet	33.25" (84 cm)
Width	66.75" (170 cm)
Depth	28.63" (73 cm)
Depth with door at 90°	30.75" (78 cm)
Capacity	18.0 cu.ft. (510 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	165.0 lbs. (75 kg)
Shipping Weight	175.0 lbs. (79 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009254
Freezer	
Door Swing	Lift-Up
Interior Height	26.25" (67 cm)
Interior Width	59.0" (150 cm)
Interior Depth	20.5" (52 cm)
Thermostat Type	Digital
Refrigerant Type	R600a
Refrigerant Amount	4.06 oz.
High Side PSI	280.0
Low Side PSI	130.0
Wheels	4
Compressor Step Height	9.25" (23 cm)
Compressor Step Width	9.38" (24 cm)
Compressor Step Depth	9.38" (24 cm)

