accuc@ld

VT65ML7ADA



32.25" x 23.63" x 23.5" (H x W x D)

Commercial freestanding medical all-freezer capable of -25° C operation, with removable basket drawers, lock, and 32 height for ADA counters

Highlights:

32" height for use in ADA compliant settings

Factory-installed lock provides security you can count on

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
ADA compliant	32 inch height for lower ADA counters	
Factory installed lock	Keep contents secure with a key lock on the door	
Fully finished white cabinet	Allows the unit to be used freestanding	
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes	
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials	
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened	
Manual defrost	Static cooling system for improved temperature stability	
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management	

accuc@ld

VT65ML7ADA Specifications:

Height of Cabinet 32.0" (81 cm) Height to Hinge Cap 32.25" (82 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.13" (115 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg) Parts & Labor Warranty 1 Year		
Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.13" (115 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.13" (115 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety ULC Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.13" (115 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Depth with door at 90° 45.13" (115 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Defrost Type Manual Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Door White Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
US Electrical Safety Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Voltage/Frequency 115 V AC/60 Hz Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Weight 105.0 lbs. (48 kg) Shipping Weight 118.0 lbs. (54 kg)		
Shipping Weight 118.0 lbs. (54 kg)		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Years		
UPC 761101043142		
Freezer		
Door Swing RHD		
Reversible Yes		
Crisper Finish Opaque		
Crisper Cover Glass		
Interior Height 24.25" (62 cm)		
Interior Width 17.75" (45 cm)		
Interior Depth 16.5" (42 cm)		
Shelf Type Glass		
Thermostat Type Digital		
Refrigerant Type R134a		
Refrigerant Amount 2.7 oz.		
High Side PSI 235.0		
Low Side PSI 70.0		
Interior Drawers Yes		
Drawers Qty 3		
Compressor Step Height 6.5" (17 cm)		

Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C
Sound Level	33 dB

