

VT65MLBISSHV



33.5" x 23.63" x 23.5" (H x W x D)

Built-in medical all-freezer capable of -25° C operation, with front lock, wrapped stainless steel door and thin handle

Highlights:

- Flexible design allows built-in or freestanding use
- 25° C operation for safe storage of temperature sensitive materials
- Stainless steel door complete with sleek handle adds modern elegance to any setting

Product Features:

Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished white cabinet	Allows the unit to be used freestanding
Height Adjustable	Adjustable legs allow the unit to be sized from 33 1/2" to 34 3/4" high
Factory installed lock	Keep contents secure with a front lock on the door
Stainless steel door	Durable design with lasting elegance
Professional stainless steel handle	Thin 14mm diameter on stainless steel handle, mounted vertically for a sleek look
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
No internal fans	Static cooling system
Manual defrost	Energy efficient operation

VT65MLBISSHV Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	126.0 lbs. (57 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101030821
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	1
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)

Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

