accuc@ld

CM411LBI7SSHVADA



32.5" x 19.25" x 21.38" (H x W x D)

Commercially listed ADA compliant 20" wide built-in refrigerator-freezer with a lock, stainless steel door, thin handle and white cabinet

Highlights:

ETL-S listed for commercial use

Flexible design allows built-in or freestanding use in 20" wide spaces

32" height fits under lower ADA compliant counters

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use	
ADA compliant	32" high to fit under lower ADA compliant counters	
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint	
Built-in capable	Make the best use of space by installing your appliance under the counter	
Fully finished white cabinet	Allows the unit to be used freestanding	
Factory installed lock	Top-mounted for convenient security	
Stainless steel wrapped door	Durable 304 grade wrapping	
Professional handle	Thin 14mm diameter on vertical stainless steel handle	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	





accuc@ld

CM411LBI7SSHVADA Specifications:

Overview		
Height of Cabinet	32.0" (81 cm)	
Height to Hinge Cap	32.5" (83 cm)	
Width	19.25" (49 cm)	
Depth	21.38" (54 cm)	
Depth with door at 90°	39.5" (100 cm)	
Capacity	4.1 cu.ft. (116 L)	
Defrost Type	Manual	
Door	Stainless Steel	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	64.0 lbs. (29 kg)	
Shipping Weight	67.0 lbs. (30 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101034805	
Refrigerator-Freezer		
Door Swing	RHD	
Reversible	Factory Reversible	
Adjustable Shelves	Yes	
Crisper Qty	1	
Crisper Finish	Transparent	
Crisper Cover	Glass	
Interior Light	Yes	
Refrigerator - Interior Height	28.75" (73 cm)	
Refrigerator - Interior Width	15.75" (40 cm)	
Refrigerator - Interior Depth	17.75" (45 cm)	
Refrigerator - Shelf Type	Wire	
Refrigerator - Shelf Qty	2	
Thermostat Type	Dial	
Refrigerant Type	R134a	

High Side PSI	205.0
Low Side PSI	103.0
Level Legs	2
Wheels	2





