

VT65MBIDPL



33.5" x 23.63" x 23.5" (H x W x D)

Built-in undercounter medical all-freezer capable of -25° C operation, with diamond plate door and towel bar handle

Highlights:

Flexible design allows built-in or freestanding use

Perfectly sized to fit under counters and in tight 24 inch spaces

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets
Fully finished white cabinet	Allows the freezer to be used freestanding
Height Adjustable	Adjustable legs allow the unit to be sized from 33 1/4" to 34 1/2" high
Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces
Diamond plate door	Textured diamond plate finish in wrapped aluminum creates a unique industrial look
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	No temperature fluctuations with an energy efficient manual defrost system
No internal fans	Temperature remains stable with a static cooling system

VT65MBIDPL Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Diamond Plate
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043029
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

