

# VT65ML7BIDPLADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant commercial built-in medical all-freezer capable of -25° C operation, with diamond plate door, towel bar handle, and lock

**Highlights:**

- ETL-S listed to NSF-7 commercial standards
- 32 inch height fits under lower ADA compliant counters
- Flexible design allows built-in or freestanding use

**Product Features:**

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
ADA Compliant	32 inch height is designed to fit under ADA compliant counters
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished white cabinet	Allows the unit to be used freestanding
Factory installed lock	Keyed lock for a secure interior
Manual defrost	Static cooling system for improved temperature stability
Diamond plate door	Textured diamond plate finish in wrapped aluminum creates a unique industrial look
Professional towel bar handle	Curved handle in polished stainless steel
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials

## VT65ML7BIDPLADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Diamond Plate
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044514
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)

Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

