

VT65ML7BIFRADA



32.25" x 23.63" x 23.5" (H x W x D)

Commercial ADA compliant built-in medical all-freezer with lock, capable of -25° C operation; door accepts slide-in panels

Highlights:

- ETL-S listed to NSF-7 commercial standards
- 32 inch height fits under lower ADA compliant counters
- Flexible design allows built-in or freestanding use

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
ADA Compliant	32 inch height is designed to fit under ADA compliant counters
Factory installed lock	Keyed lock for a secure interior
Stainless steel door frame	Two-piece U-shaped door frame in stainless steel accepts slide-in panels, allowing users to create a custom look to match or complement adjacent cabinetry
Pro style handle	Stainless steel handle adds an attractive touch
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished white cabinet	Allows the unit to be used freestanding
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static cooling system for improved temperature stability

VT65ML7BIFRADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044521
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.0" (15 cm)

Temperature Range

