

CM411LMED



34" x 19.25" x 21.38" (H x W x D)

20" wide counter height refrigerator-freezer with a lock, temperature alarm, interior fan and hospital grade cord

Highlights:

- Slim 20" width is ideal for any setting
- Factory installed lock provides security you can count on
- High temperature alarm includes external temperature readout

Product Features:

Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Fully finished white cabinet	Allows the unit to be used freestanding
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Factory installed lock	Keyed lock for secure interior
Manual defrost	Efficient performance with reliable temperature stability
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Internal fan with heat sink	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup
Interior light	Turn the light on and off with a convenient rocker switch

CM411LMED Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with Handle	23.0" (58 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Shipping Weight	85.0 lbs. (39 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101032993
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Adjustable Shelves	Yes
Interior Light	Yes
Refrigerator - Interior Height	28.75" (73 cm)
Refrigerator - Interior Width	15.75" (40 cm)
Refrigerator - Interior Depth	17.75" (45 cm)
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	2
Thermostat Type	Dial
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	1.75 oz.
High Side PSI	205.0
Low Side PSI	103.0

Level Legs

Wheels

