# **SBC695OSNCFTWIN**



#### 34.25" x 23.75" x 25" (H x W x D)

Outdoor/indoor commercial nitro-infused dual tap coffee dispenser for built-in or freestanding use, with complete tap kit, digital thermostat, and 304 grade stainless steel exterior

#### **Highlights:**

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Commercial grade dual style tap kit includes everything you need to serve creamy nitro-infused coffee on draft

### **Product Features:**

Dispenses nitro-infused coffee	Stout style tap allows you to serve smooth nitro-infused cold brew on tap	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Weatherproof design	Solid construction allows placement in the outdoors	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Full-sized coffee dispenser	Large interior can accept up to three cornelius kegs	
Complete tap kit	Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs	
Stainless steel exterior	Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors	
Professional handle	Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





## SBC695OSNCFTWIN Specifications:

Overview		
Height of Cabinet	34.25" (87 cm)	
Width	23.75" (60 cm)	
Depth	25.0" (64 cm)	
Depth with Handle	26.88" (68 cm)	
Depth with door at 90°	47.75" (121 cm)	
Capacity	6.04 cu.ft. (171 L)	
Defrost Type	Automatic	
Door	Stainless Steel	
Cabinet	Stainless Steel	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.3	
Voltage/Frequency	115 V AC/60 Hz	
Weight	108.0 lbs. (49 kg)	
Shipping Weight	113.0 lbs. (51 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101060996	
Kegerator		
Door Swing	RHD	
Reversible	Yes	
Tap Kit	Yes	
Height with Tap	50.38" (128 cm)	
Number of Taps	2	
Thermostat Type	Digital	
Interior Light	Yes	
Fan Type	Interior and Exterior	
Refrigerant	R600a	
Refrigerant Amount	1.76 oz.	
High Side PSI	220.0	
Low Side PSI	43.0	
Intor I loight	27.0" (69 cm)	
Inter Height		
Inter Height Interior Width	20.38" (52 cm)	
	20.38" (52 cm) 21.25" (54 cm)	
Interior Width		
Interior Width Interior Depth	21.25" (54 cm)	

Compressor Step Depth	2.5" (6 cm)
Wheel Qty	4
Surface	Stainless Steel
Temperature Range	32º to 50ºF



