

FF511L7CSSADA



32.5" x 19.25" x 21.38" (H x W x D)

Commercially listed ADA Compliant 20" wide built-in undercounter all-refrigerator in complete stainless steel, auto defrost with a lock

Highlights:

ETL-S listed for commercial use

Flexible design allows built-in or freestanding use in 20" wide spaces

Fully wrapped in 304 grade stainless steel, with a curved towel bar handle

Product Features:

Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Commercially listed	ETL-S listed to NSF standards for commercial use
ADA compliant	32" high to fit under lower ADA compliant counters
Built-in capable	Make the best use of space by installing your appliance under the counter
Complete stainless steel exterior	304 grade stainless steel on the cabinet and door
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip
Factory installed lock	Top-mounted for convenient security
Fully finished cabinet	Allows the unit to be used freestanding
Automatic defrost	Reduced maintenance with auto defrost system

FF511L7CSSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.5" (83 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	72.0 lbs. (33 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101008141
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Crisper Qty	1
Crisper Finish	Transparent
Crisper Cover	Glass
Shelf Type	Wire
Shelf Qty	2
Full Door Shelf Qty	1
Half Door Shelf Qty	2
Adjustable Shelves	Yes
Can Storage	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.9oz.
High Side PSI	250.0
Low Side PSI	110.0
Level Legs Qty	2
Interior Light	Yes

Dimensions	
Interior Height	28.5" (72 cm)
Interior Width	15.75" (40 cm)
Interior Depth	18.0" (46 cm)
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	16.5" (42 cm)
Compressor Step Depth	5.5" (14 cm)

