## accuceld

# **FF511LBIVAC**



#### 34" x 19.25" x 22.25" (H x W x D)

Built-in undercounter medical all-refrigerator for temperature stable medical storage, with interior basket drawers, internal fan, lock, and more

#### **Highlights**:

Medical grade design conforms with CDC guidelines for vaccine storage

Interior drawers ensure stored items are not exposed to room temperature when the door is open

Automatic defrost with an internal fan for stabilized cooling designed to stay within 2°C of set temperature

#### **Product Features:**

Improved temperature stability	Interior is designed to operate within 2°C of set temperature performance
Interior basket drawers	Three slide-out plastic drawers offer convenient storage solutions while protecting stored items when the door is open
Digital thermostat	Electronic controls ensure easy and intuitive temperature management
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarm includes NIST calibrated display of the current interior and high/low temperature
Self-closing door	Door closes automatically when opened at angles less than 90°
Access port with contact	Pre-installed probe with contact allows users to install their own monitoring equipment; customers can specify placement of the access port upon order
Hospital grade cord with 'green dot' plug	Secure three-pronged 'green dot' cord for added unit safety in high traffic settings
Automatic defrost	Reduced maintenance with auto defrost system

 $\checkmark$ 



### accuceld

#### **FF511LBIVAC Specifications:**

Canadian Electrical ETL Safety	rm) rm) rm) cm) L) atic hite
Width19.25" (49 cDepth22.25" (57 cDepth with door at 90°39.5" (100 cCapacity2.5 cu.ft. (71Defrost TypeAutomaDoorWhCabinetWhUS Electrical SafetyECanadian ElectricalETLSafetyE	rm) rm) cm) L) atic nite
Depth22.25" (57 cDepth with door at 90°39.5" (100 cCapacity2.5 cu.ft. (71Defrost TypeAutomaDoorWhCabinetWhUS Electrical SafetyECanadian ElectricalETLSafety	m) L) atic nite
Depth with door at 90°39.5" (100 cCapacity2.5 cu.ft. (71Defrost TypeAutomaDoorWhCabinetWhUS Electrical SafetyECanadian ElectricalETLSafetyE	m) L) atic nite
Capacity2.5 cu.ft. (71)Defrost TypeAutomaDoorWhCabinetWhUS Electrical SafetyECanadian ElectricalETLSafetyE	L) atic nite nite
Defrost Type Automa   Door Wh   Cabinet Wh   US Electrical Safety E   Canadian Electrical ETL   Safety E	atic nite nite
Door Wh   Cabinet Wh   US Electrical Safety E   Canadian Electrical ETL   Safety E	nite nite TL
Cabinet Wh US Electrical Safety E Canadian Electrical ETL Safety	nite TL
US Electrical Safety E Canadian Electrical ETL Safety	TL
Canadian Electrical ETL Safety	
Safety	C
Amps	
	1.4
Voltage/Frequency 115 V AC/60	Hz
Weight 75.0 lbs. (34 l	kg)
Parts & Labor Warranty 2 Yea	ars
Compressor Warranty 5 Yea	ars
UPC 7611010355	605
Refrigerator Features	
Door Swing RI	HD
Reversible Factory Reversil	ble
Height Adjustable	1
Thermostat Type Dig	ital
Fan Type Interior a Exter	
Refrigerant Type R13	4a
Refrigerant Amount 1.75	oz.
High Side PSI 205	5.0
Low Side PSI 103	3.0
Level Legs Qty	2
	/es
Interior Drawers	3
Interior Drawers Qty	



