

FF6LBI7PLUS



33.5" x 23.63" x 23.5" (H x W x D)

Commercially approved 24" wide auto defrost all-refrigerator for built-in use, with a thermometer, internal fan, and front lock

Highlights:

Includes adjustable glass shelves for flexible storage

Flexible design allows built-in or freestanding use in 24" wide spaces

Commercially listed to NSF-7 standards

Product Features:

Commercially approved	ETL-S listed to NSF standards for commercial use
Built-in capable	Make the best use of space by installing your appliance under the counter
Fully finished white cabinet	Allows the unit to be used freestanding
Height Adjustable	Adjustable legs allow the unit to be sized from 33 1/2" to 34 3/4" high
Factory installed lock	Keyed lock for secure interior
Automatic defrost	Reduced maintenance with auto defrost system
Thermometer	Thermometer provides external readout of current and high/low temperatures
Internal fan with heat sink	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
Adjustable glass shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup

FF6LBI7PLUS Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044927
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Full Door Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Interior and Exterior
Refrigerant Type	R134a
Refrigerant Amount	1.8oz.
High Side PSI	285.0
Low Side PSI	70.0
Level Legs Qty	4
Interior Light	Yes
Dimensions	
Interior Height	27.75" (70 cm)
Interior Width	20.0" (51 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)

Compressor Step Depth

