

FF7BSSHHADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant commercial all-refrigerator for freestanding general purpose use, auto defrost w/SS door, horizontal handle, and black cabinet

Highlights:

Commercially approved for use in foodservice establishments

32" height for use in ADA compliant settings

Stainless steel door complete with sleek horizontal handle adds luxury to any setting

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
ADA compliant	32" height for use in settings complying with ADA guidelines for lower counter height	
Slim counter height dimensions	Less than 24 inches wide with a full 5.5 c.f. capacity	
Fully finished black cabinet	Allows the refrigerator to be used freestanding	
Stainless steel door	Durable design with lasting elegance	
Professional horizontal handle	Thin 14mm diameter on stainless steel handle set horizontally across the door	
Automatic defrost	Reduced user maintenance with automatic defrost	
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices	
Adjustable glass shelves	Rearrange the refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up	



FF7BSSHHADA Specifications:

Overview Height of Cabinet 32.0" (81 cm) Height to Hinge Cap 32.25" (82 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety ULC Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Height to Hinge Cap 32.25" (82 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety ULC Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety ULC Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth 23.5" (60 cm) Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety ULC Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth with Handle 24.25" (62 cm) Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Depth with door at 90° 45.0" (114 cm) Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Capacity 5.5 cu.ft. (156 L) Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Defrost Type Automatic Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Door Stainless Steel Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
CabinetBlackUS Electrical SafetyULCanadian Electrical SafetyULCSanitationETL-SAmps1.3Voltage/Frequency115 V AC/60 HzWeight100.0 lbs. (45 kg)		
US Electrical Safety Canadian Electrical Safety Sanitation ETL-S Amps 1.3 Voltage/Frequency Weight ULC 115 V AC/60 Hz		
Canadian Electrical SafetyULCSanitationETL-SAmps1.3Voltage/Frequency115 V AC/60 HzWeight100.0 lbs. (45 kg)		
Safety ETL-S Sanitation ETL-S Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Amps 1.3 Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Voltage/Frequency 115 V AC/60 Hz Weight 100.0 lbs. (45 kg)		
Weight 100.0 lbs. (45 kg)		
D		
Parts & Labor Warranty 1 Year		
Compressor Warranty 5 Years		
UPC 761101048031		
Refrigerator Features		
Door Swing RHD		
Reversible Yes		
Shelf Type Glass		
Shelf Qty 3		
Adjustable Shelves Yes		
Thermostat Type Dial		
Refrigerant Type R134a		
Refrigerant Amount 1.8oz.		
High Side PSI 285.0		
Low Side PSI 88.0		
Level Legs Qty 4		
Interior Light Yes		
Dimensions		
Interior Height 26.25" (67 cm)		
Interior Width 21.0" (53 cm)		
Interior Depth 17.75" (45 cm)		
Compressor Step Height 5.5" (14 cm)		

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)

