

FF7LBLFR



33.5" x 23.63" x 23.5" (H x W x D)

Commercially listed freestanding all-refrigerator for general purpose use, auto defrost w/SS door frame for slide-in panels, lock, and black cabinet

Highlights:

Commercially approved for use in foodservice establishments

Factory-installed lock provides security you can count on

Full 5.5 cu.ft. capacity inside a convenient 24" footprint

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Slim counter height dimensions	Less than 24 inches wide with a full 5.5 c.f. capacity
Fully finished black cabinet	Allows the refrigerator to be used freestanding
Stainless steel door frame	Slide a panel into this two-piece U-shaped frame to match your unit to other cabinets (panel size: 23" W x 28" H)
Factory installed lock	Keyed lock for a secure interior
Professional handle	Stainless steel handle can be reversed with door swing
Reversible door	User-reversible door swing for added flexibility
Automatic defrost	Reduced maintenance with auto defrost system
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices

FF7LBLFR Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.63" (63 cm)
Depth with door at 90°	45.13" (115 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101013619
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Glass
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.8oz.
High Side PSI	285.0
Low Side PSI	70.0
Level Legs Qty	4
Interior Light	Yes
Dimensions	
Interior Height	27.75" (70 cm)
Interior Width	20.0" (51 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	6.0" (15 cm)

