accuc@ld

FF7LCSSADA



32.25" x 23.75" x 23.25" (H x W x D)

ADA compliant built-in undercounter all-refrigerator for general purpose or commercial use, auto defrost w/SS wrapped exterior, towel bar handle, and lock

Highlights:

Commercially approved for use in foodservice establishments

32" height allows installation under lower ADA compliant counters

Complete stainless steel construction adds luxury to any setting

Product Features:

| ETL-S listed to NSF-7 Standards for use in commercial establishments |
|---------------------------------------------------------------------------------------------------------|
| 32 inch height fits under standard ADA counters |
| Ideal 24" footprint offers full 5.5 cu.ft. storage capacity in a slim fit |
| Make the best use of space by installing your appliance under the counter and flush with other cabinets |
| Allows the refrigerator to be used freestanding |
| Keyed lock for a secure interior |
| Durable design with lasting elegance |
| Curved handle in brushed stainless steel offers a sturdy grip with professional elegance |
| Reduced user maintenance with automatic defrost |
| |



accuc@ld

FF7LCSSADA Specifications:

| Overview | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.75" (60 cm) |
| Depth | 23.25" (59 cm) |
| Depth with Handle | 25.25" (64 cm) |
| Depth with door at 90° | 45.5" (116 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Sanitation | ETL-S |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 100.0 lbs. (45 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101013879 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| | |
| Shelf Type | Wire |
| Shelf Type Shelf Qty | Wire 3 |
| | |
| Shelf Qty | 3 |
| Shelf Qty Adjustable Shelves | 3 Yes |
| Shelf Qty Adjustable Shelves Thermostat Type | 3 Yes Dial |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type | 3 Yes Dial Exterior |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type | 3 Yes Dial Exterior R134a |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount | 3 Yes Dial Exterior R134a 1.8oz. |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI | 3 Yes Dial Exterior R134a 1.8oz. 285.0 |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI | 3 Yes Dial Exterior R134a 1.8oz. 285.0 70.0 |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty | 3 Yes Dial Exterior R134a 1.8oz. 285.0 70.0 |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light | 3 Yes Dial Exterior R134a 1.8oz. 285.0 70.0 |
| Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Dimensions | 3 Yes Dial Exterior R134a 1.8oz. 285.0 70.0 4 Yes |

| Compressor Step Height | 7.0" (18 cm) |
|------------------------|---------------|
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 6.0" (15 cm) |



