## accuc@ld

# FFAR10FC7MED



55.5" x 23.63" x 23.5" (H x W x D)

Discontinued: Replaced by FFAR10MED

### **Highlights:**

Over 10 cu.ft. of storage in a slim 24" footprint

Fully featured for use in medical and laboratory settings

Alarm warns of temperature variations while providing a digital display of interior temperature

#### **Product Features:**

Commercially approved	ETL-S listed to NSF standards for commercial use	
Thin-line design	Limited space is no problem for our thin-line models, designed specifically for those hard-to-fit spots	
Large capacity	10.1 cu.ft. capacity in a 24" footprint	
Automatic defrost	Reduced maintenance with auto defrost system	
Side-mounted lock	Keep contents secure with a key lock on the side	
Internal fan with heat sink	Fan-forced cooling ensures the unit is evenly cooled from top to bottom	
Hospital grade cord	Secure three-pronged cord for added unit safety	
Alarm with temperature display	Temperature alarm warns of interior fluctuations while providing an external temperature readout on the door	
Adjustable wire shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up	



## accuc@ld

### **FFAR10FC7MED Specifications:**

Height of Cabinet 55.13" (140 cm) Height to Hinge Cap 55.5" (141 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 24.75" (63 cm) Depth with door at 90° 45.5" (116 cm) Capacity 10.1 cu.ft. (286 L) Defrost Type Automatic Door White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-5 Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Yea			
Width 23.63" (60 cm)  Depth 23.5" (60 cm)  Depth with Handle 24.75" (63 cm)  Depth with door at 90° 45.5" (116 cm)  Capacity 10.1 cu.ft. (286 L)  Defrost Type Automatic  Door White  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Other Energy Info 120 Volts / 60 Hz  Amps 1.5  Voltage/Frequency 115 V AC/60 Hz  Parts & Labor Warranty 1 Year			
Depth 23.5" (60 cm. Depth with Handle 24.75" (63 cm. Depth with door at 90° 45.5" (116 cm. Capacity 10.1 cu.ft. (286 L. Defrost Type Automatic Door White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Year			
Depth with Handle 24.75" (63 cm) Depth with door at 90° 45.5" (116 cm) Capacity 10.1 cu.ft. (286 L) Defrost Type Automatic Door White US Electrical Safety ULC Canadian Electrical Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Year			
Depth with door at 90° 45.5" (116 cm) Capacity 10.1 cu.ft. (286 L) Defrost Type Automatic  Door White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Year			
Capacity 10.1 cu.ft. (286 L)  Defrost Type Automatic  Door White  Cabinet White  US Electrical Safety ULC  Canadian Electrical Safety Sanitation ETL-S  Other Energy Info 120 Volts / 60 Hz  Amps 1.5  Voltage/Frequency 115 V AC/60 Hz  Parts & Labor Warranty 1 Year			
Defrost Type Automatic  Door White  Cabinet White  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Other Energy Info 120 Volts / 60 Hz  Amps 1.5  Voltage/Frequency 115 V AC/60 Hz  Parts & Labor Warranty 1 Year			
Door White Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Year			
Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Year			
US Electrical Safety  Canadian Electrical Safety  Sanitation  ETL-S  Other Energy Info  Amps  1.5  Voltage/Frequency  Parts & Labor Warranty  ULC  100  110  ETL-S  120  120  120  130  140  150  150  170  170  170  170  170  17			
Canadian Electrical Safety  Sanitation  ETL-S  Other Energy Info  Amps  1.5  Voltage/Frequency  Parts & Labor Warranty  ULC  120 Volts  60 Hz  15 V AC/60 Hz  17 Year			
Safety Sanitation ETL-S Other Energy Info 120 Volts / 60 Hz Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Yea			
Other Energy Info  Amps  1.5  Voltage/Frequency  Parts & Labor Warranty  120 Volts / 60 Hz  1.5  1.5  1.5  1.5  1.5  1.5  1.5  1.			
Amps 1.5 Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Yea			
Voltage/Frequency 115 V AC/60 Hz Parts & Labor Warranty 1 Yea			
Parts & Labor Warranty 1 Year			
<u> </u>			
Compressor Warranty 5 Years			
UPC 761101001142			
Refrigerator Features			
Door Swing RHD			
Reversible Factory Reversible			
Shelf Type Wire			
Shelf Qty			
Adjustable Shelves Yes			
Thermostat Type Dia			
Fan Type Interio			
5 (1 ) =			
Refrigerant Type R134a			
Refrigerant Type R134a Refrigerant Amount 3.0oz			
Refrigerant Amount 3.0oz			
Refrigerant Amount 3.0oz High Side PSI 290.0			
Refrigerant Amount 3.0oz High Side PSI 290.0 Low Side PSI 70.0			
Refrigerant Amount 3.0oz High Side PSI 290.0 Low Side PSI 70.0 Level Legs Qty 2			
Refrigerant Amount 3.0oz High Side PSI 290.0 Low Side PSI 70.0 Level Legs Qty 2 Interior Light Yes			
Refrigerant Amount 3.0oz High Side PSI 290.0 Low Side PSI 70.0 Level Legs Qty 2 Interior Light Yes Dimensions			

Compressor Step Height	6.25" (16 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.5" (14 cm)



