

FFAR22L7CSSPLUS



20.5" x 17.38" x 19.9" (H x W x D)

DISCONTINUED: Replaced by FFAR22LW7CSSPLUS

Highlights:

Medical grade design conforms with CDC guidelines for vaccine storage

Factory installed lock provides security you can count on

Commercially listed to NSF-7 standards

Product Features:

Commercially listed	CSA-S listed to NSF-7 standards
Automatic defrost	Reduced maintenance with auto defrost system
100% CFC Free	Environmentally friendly design with no ozone-damaging chemicals
Factory installed lock	Keyed lock for secure interior
Thermometer	Thermometer provides external readout of current and high/low temperatures
Internal fan with heat sink	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
Removable shelf	Wired shelf provided
Removable shelf	Wired shelf provided
Adjustable thermostat	Rear mounted to prevent accidental adjustments

FFAR22L7CSSPLUS Specifications:

Overview	
Height of Cabinet	20.18" (51 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.9" (51 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	CSA
Canadian Electrical Safety	CSA
Sanitation	CSA-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	35.3 lbs. (16 kg)
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Interior
Refrigerant Type	R134a
Refrigerant Amount	1.94oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs Qty	2
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	14.18" (36 cm)
Interior Depth	14.5" (37 cm)
Compressor Step Height	6.75" (17 cm)
Compressor Step Width	14.18" (36 cm)
Compressor Step Depth	5.25" (13 cm)

