

ALF620LSSHV



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant freestanding medical all-freezer capable of -25° C operation, with lock, wrapped stainless steel door and thin handle

Highlights:

Designed for use in medical facilities

32 inches high to meet ADA guidelines for lower counter height

-25°C operation for safe storage of temperature sensitive materials

Product Features:

ADA Compliant	32 inch height is designed to meet ADA guidelines for lower counter height
Slim counter height dimensions	Less than 24 inches wide to fit tight spaces
Factory installed lock	Keyed lock offers added security
Fully finished white cabinet	Allows the unit to be used freestanding
Stainless steel door	304 grade stainless steel wrapped door for lasting durability
Professional stainless steel handle	Thin 14mm diameter on stainless steel handle, mounted vertically for a sleek look
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Manual defrost	Static cooling system reduces temperature fluctuations

ALF620LSSHV Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	95.0 lbs. (43 kg)
Shipping Weight	98.0 lbs. (44 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101004617
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

