

FS20L7CSS



19.75" x 19.75" x 19.38" (H x W x D)

Commercially approved compact "cube" shaped all-freezer with a front-mounted lock and complete stainless steel exterior, capable of -20°C operation

Highlights:

- Commercially approved for use in foodservice establishments
- Compact "cube" size for easy placement above counters
- 20° C capable for sensitive storage

Product Features:

| | |
|-----------------------------------|--|
| Commercially approved | ETL-S listed to ANSI-NSF Standard 7 and CalCode Compliant |
| Complete stainless steel exterior | Unit is fully wrapped in 304 grade stainless steel for durable luxury |
| Fully finished cabinet | Allows the unit to be used freestanding |
| Cube shaped | Square footprint for placement on top of counters |
| Factory installed lock | Keyed lock for a secure interior |
| -20° C capable | Operates at safe temperature for storage of select sensitive material |
| Manual defrost | Static cooling system for improved temperature stability |
| One piece interior liner | Easy clean-up with a seamless liner that won't hold a mess in hidden crevices |
| Flat door liner | Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials |

FS20L7CSS Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 19.75" (50 cm) |
| Width | 19.75" (50 cm) |
| Depth | 19.38" (49 cm) |
| Depth with door at 90° | 37.88" (96 cm) |
| Capacity | 1.6 cu.ft. (45 L) |
| Defrost Type | Manual |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Sanitation | ETL-S |
| Amps | 1.43 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101008356 |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Interior Height | 14.5" (37 cm) |
| Interior Width | 15.5" (39 cm) |
| Interior Depth | 15.0" (38 cm) |
| Shelf Qty | 1 |
| Adjustable Shelves | Yes |
| Thermostat Type | Dial |
| Refrigerant Type | R134a |
| Refrigerant Amount | 3.17 oz. |
| High Side PSI | 250.0 |
| Low Side PSI | 88.0 |
| Level Legs | 2 |
| Compressor Step Height | 8.5" (22 cm) |
| Compressor Step Width | 15.5" (39 cm) |
| Compressor Step Depth | 7.0" (18 cm) |

