

# FS20L7CSSMED



19.75" x 19.75" x 19.38" (H x W x D)

Commercially listed compact -20°C all-freezer in stainless steel, with lock, alarm with temperature display, and hospital grade cord

**Highlights:**

- Commercially listed to NSF-7 standards
- Factory installed lock provides security you can count on
- 20°C capable with manual defrost operation

**Product Features:**

Commercially approved	ETL-S listed to NSF standards for commercial use
Compact dimensions	Ideal size for use on top of counters
Complete stainless steel exterior	Fully wrapped in 304 grade stainless steel
-20° capable	Low temperature capability ideal for certain sensitive items
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Manual defrost	Efficient performance with reliable temperature stability
Removable shelf	Wired shelf provided
Adjustable thermostat	Manage the temperature with ease and accuracy

## FS20L7CSSMED Specifications:

Overview	
Height of Cabinet	19.75" (50 cm)
Width	19.75" (50 cm)
Depth	19.38" (49 cm)
Depth with door at 90°	37.88" (96 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044378
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

