

FS20L7CSSMEDDT



20.75" x 19.75" x 21" (H x W x D)

Commercially approved compact stainless steel all-freezer, with digital thermostat, lock, alarm with temperature display, and hospital grade cord

Highlights:

Commercially listed to NSF-7 standards and CalCode compliant

Compact cube size is ideal for countertop use

Digital thermostat allows more precision in temperature control

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
Compact dimensions	Ideal size for use on top of counters
-20° capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Factory installed lock	Keyed lock for secure interior
Complete stainless steel exterior	Fully wrapped in 304 grade stainless steel
Digital thermostat	Electronic controls for more precise temperature management
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety

FS20L7CSSMEDDT Specifications:

Overview	
Height of Cabinet	20.75" (53 cm)
Height to Hinge Cap	20.75" (53 cm)
Width	19.75" (50 cm)
Depth	21.0" (53 cm)
Depth with Handle	21.0" (53 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101044040
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

