

FS20L7CSSPLUS



19.75" x 19.75" x 19.38" (H x W x D)

Commercially approved compact all-freezer in stainless steel, manual defrost with a lock and thermometer

Highlights:

Commercially listed to NSF-7 standards

Thermometer provides external readout of current and high/low temperature

-20°C capable with manual defrost operation

Product Features:

Commercially approved	ETL-S listed to NSF standards for commercial use
Factory installed lock	Keyed lock for secure interior
Compact dimensions	Compact 20" footprint for placement on counters
-20° capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Thermometer	Thermometer provides external readout of current and high/low temperatures
Complete stainless steel exterior	Fully wrapped in 304 grade stainless steel
Removable shelf	Wired shelf provided
100% CFC Free	Environmentally friendly design with no ozone-damaging chemicals

FS20L7CSSPLUS Specifications:

Overview	
Height of Cabinet	19.75" (50 cm)
Width	19.75" (50 cm)
Depth	19.38" (49 cm)
Depth with door at 90°	37.88" (96 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

