

ALF620SSH



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant freestanding medical all-freezer capable of -25° C operation, with wrapped stainless steel door and horizontal handle

Highlights:

- Designed for use in medical facilities
- 32" high to meet ADA guidelines for lower counters
- 25°C operation for safe storage of temperature sensitive materials

Product Features:

ADA compliant	32" high for use in ADA compliant settings
Fully finished white cabinet	Allows the unit to be used freestanding
Slim counter height dimensions	Less than 24" wide to fit tight spaces
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static and stable cooling with no internal fans
Three slide-out drawers	Wired baskets allow optimum airflow, with plastic drawer fronts to keep contents cold when the door is opened
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes
Stainless steel door	304 grade stainless steel wrapped door for lasting durability
Professional horizontal handle	Thin stainless steel handle with a 14mm diameter matches many popular styles of cabinetry handles

ALF620SSH Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	95.0 lbs. (43 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009759
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

