

FS22L7



20.5" x 17.38" x 19" (H x W x D)

Compact commercially listed all-freezer with lock, capable of -20°C operation

Highlights:

Commercially listed to NSF-7 standards

-20° C capable for sensitive storage

Seamless interior liner simplifies cleanup

Product Features:

Commercially listed	CSA-S listed to NSF standards for commercial use
Fully finished white cabinet	Allows the unit to be used freestanding
Factory installed lock	Keyed lock for a secure interior
-20° C capable	Operates at safe temperature for storage of select sensitive material
Manual defrost	Static cooling system for improved temperature stability
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes
Adjustable thermostat	Rear mounted to prevent accidental adjustments
Removable shelf	Wire shelf for storage convenience
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

FS22L7 Specifications:

Overview	
Height of Cabinet	20.13" (51 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.0" (48 cm)
Capacity	1.42 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	CSA
Sanitation	CSA-S
Energy Usage/Year	272.0kWh/year
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101034003
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	14.63" (37 cm)
Interior Width	12.38" (31 cm)
Interior Depth	14.5" (37 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.67 oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs	2
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	12.38" (31 cm)
Compressor Step Depth	6.0" (15 cm)

