

FS22L7FROST



20.5" x 17.38" x 19" (H x W x D)

Compact commercial beer froster with digital thermostat preset to 24° F and front lock

Highlights:

Commercially listed to NSF-7 standards

Enjoy ice cold aluminum bottled beer stored at approximately 24° F

Precise temperature control with a digital thermostat

Product Features:

Commercially listed	CSA-S listed to NSF standards for commercial use
24° F pre-set operation	Ideal temperature to hold aluminum bottled beer just above its freezing point
Digital thermostat	Precise temperature management at the touch of a button
Factory installed lock	Keep contents secure with a key lock on the door
Manual defrost	No temperature fluctuations with a manual defrost system that keeps the cold inside
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes
Removable shelf	Wire shelf for storage convenience
One piece interior liner	Enjoy easy clean-up with a seamless liner that won't hold a mess in hidden crevices
100% CFC free	Environmentally friendly design without ozone-damaging chemicals

FS22L7FROST Specifications:

Overview	
Height of Cabinet	21.5" (55 cm)
Height to Hinge Cap	20.5" (52 cm)
Width	17.38" (44 cm)
Depth	19.0" (48 cm)
Capacity	1.42 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	CSA
Sanitation	CSA-S
Energy Usage/Year	272.0kWh/year
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101041315
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	14.63" (37 cm)
Interior Width	12.38" (31 cm)
Interior Depth	14.5" (37 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	1.67 oz.
High Side PSI	270.0
Low Side PSI	103.0
Level Legs	2
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	12.38" (31 cm)
Compressor Step Depth	6.0" (15 cm)

