

# FS30LPLUS



24.63" x 18.5" x 17.75" (H x W x D)

Compact manual defrost all-freezer for medical/general purpose use, with external thermometer and lock

**Highlights:**

- Compact size is ideal for countertop use
- Thermometer provides NIST calibrated external readout of current and high/low temperature
- Factory installed lock provides added security

**Product Features:**

Compact dimensions	Sized for easy use on top of counters
Factory installed lock	Keyed lock for a secure interior
NIST calibrated thermometer	Thermometer provides external readout of current and high/low temperatures
Manual defrost	Static cooling system for improved temperature stability
-20°C capable	Low temperature capability ideal for certain sensitive items
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

## FS30LPLUS Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101041346
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

