

FS408BL7SSHH



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide counter height all-freezer, -20° C capable with a lock, stainless steel door, horizontal handle and black cabinet

Highlights:

Slim 20" width is ideal for any setting

ETL-S listed for commercial use

-20° C capable with interior slide-out drawers for easy storage

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use	
Slim 20" width	2.8 capacity inside a slim footprint	
Fully finished black cabinet	Allows the unit to be used freestanding	
Factory installed lock	Top-mounted for convenient security	
Stainless steel wrapped door	Durable 304 grade wrapping	
Professional horizontal handle	Thin 14mm diameter on stainless steel handle, mounted horizontally on the door	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Manual defrost	Efficient performance with reliable temperature stability	
-20° capable	Low temperature capability ideal for certain sensitive items	







FS408BL7SSHH Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Height to Hinge Cap	34.0" (86 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	2.8 cu.ft. (79 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.6
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101041681
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	26.38" (67 cm)
Interior Width	14.0" (36 cm)
Interior Depth	16.75" (43 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.0 oz.
High Side PSI	210.0
Low Side PSI	105.0
Level Legs	2
Interior Drawers	Yes
	4



