# accuc@ld

# **FS40LMED**



33.25" x 19.38" x 22" (H x W x D)

DISCONTINUED: For a similar unit, see the FS407LMED

### **Highlights:**

Slim 20 inch width fits easily in any setting

Specially featured for use in medical and laboratory facilities

Factory installed lock provides security you can count on

#### **Product Features:**

Commercially approved	ETL-S Listed and CalCode Compliant	
Thin-line width	Limited space is no problem for our thin-line models, designed for easy placement in tight settings	
Fully finished white cabinet	Allows the unit to be used freestanding	
Factory installed lock	Keep contents secure with a front lock on the door	
Hospital grade cord and plug	Green dot plug for added safety	
Alarm with temperature display	Temperature alarm warns of interior fluctuations while providing an external temperature readout on the door	
Adjustable thermostat	Manage the temperature with ease and accuracy	
No internal fans SUMMIT APPLIANCE DIVISION, FELIX S	Static cooling system	
	EL 718-89 程序的文序各样的合格对象 Sentimed www.summitappliance.co	

# accuc@ld

## **FS40LMED Specifications:**

Overview		
Height of Cabinet	33.25" (84 cm)	
Width	19.38" (49 cm)	
Depth	22.0" (56 cm)	
Defrost Type	Manual	
Door	White	
Cabinet	White	
US Electrical Safety	UL	
Weight	80.0 lbs. (36 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101015484	
Freezer		
Door Swing	RHD	
Reversible	Factory Reversible	



