

## SBC4907FR



51.38" x 23.63" x 24.88" (H x W x D)

Commercially approved freestanding beer dispenser with complete tap kit, black cabinet, and stainless steel frame for custom panels

## **Highlights:**

Commercially approved for use in food service establishments

Accepts half, quarter, and mini kegs of your favorite brew

Customize the unit by inserting a panel into the stainless steel door frame

## **Product Features:**

| Commercially approved  | ETL-S Listed to NSF-18   |
|--|--|
| Full-sized beer dispenser  | Interior accommodates half, quarter, or mini (pony) kegs   |
| Fully finished black cabinet   | Allows the unit to be used freestanding  |
| KIT 490 included   | Complete tap system with 5 lb. CO2 tank and regulator, draft arm, Sankey American tap, connection hardware, and cleaning kit   |
| Stainless steel door frame   | Slide a panel into this two-piece exposed stainless steel door frame to match the unit to other cabinetry  |
| Professional handle  | Stainless steel handle for durable elegance  |
| Automatic defrost  | Reduced user maintenance with auto defrost operation   |
| Adjustable thermostat SUMMIT APPLIANCE DIVISION, FELIX ST CASTETIS ON CHARGE OF THE ST CAST OF T | Manage the temperature with ease and accuracy TORCH, INC.  ISO 9001:2015 Certified L 718-89¥39୩୧ak€ ୪୮୫୯୪୮୩୮୭୪୧୧able, inst ™ist ରେଖିଟେଡ଼ା ଅଧ୍ୟକ୍ତ to the t ₩ ১ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ ৬ |



## **SBC4907FR Specifications:**

| Overview                                |                                |  |
|---|--------------------------------|--|
| Height of Cabinet                       | 51.38" (131 cm)                |  |
| Width                                   | 23.63" (60 cm)                 |  |
| Depth                                   | 24.88" (63 cm)                 |  |
| Depth with Handle                       | 26.5" (67 cm)                  |  |
| Depth with door at 90°                  | 47.0" (119 cm)                 |  |
| Capacity                                | 6.4 cu.ft. (181 L)             |  |
| Defrost Type                            | Automatic                      |  |
| Door                                    | Panel-Ready                    |  |
| Cabinet                                 | Black                          |  |
| US Electrical Safety                    | UL                             |  |
| Canadian Electrical Safety              | ULC                            |  |
| Sanitation                              | ETL-S                          |  |
| Amps                                    | 1.7                            |  |
| Voltage/Frequency                       | 115 V AC/60 Hz                 |  |
| Parts & Labor Warranty                  | 1 Year                         |  |
| Compressor Warranty                     | 5 Years                        |  |
| UPC                                     | 761101015729                   |  |
| Kegerator                               |                                |  |
| Door Swing                              | RHD                            |  |
| Reversible                              | No                             |  |
| Shelf Type                              | Wire                           |  |
| Shelf Qty                               | 2                              |  |
| Thermostat Type                         | Dial                           |  |
| Refrigerant                             | R134a                          |  |
|   |                                |  |
| Refrigerant Amount                      | 2.1 oz.                        |  |
| Refrigerant Amount High Side PSI        | 2.1 oz.<br>280.0               |  |
|   |                                |  |
| High Side PSI                           | 280.0                          |  |
| High Side PSI Low Side PSI              | 280.0<br>88.0                  |  |
| High Side PSI Low Side PSI Inter Height | 280.0<br>88.0<br>29.0" (74 cm) |  |



