

SCF1076PDC



48.5" x 42.63" x 27" (H x W x D)

Deluxe dipping cabinet with polycarbonate sneeze guard and digital thermostat

Highlights:

Deluxe dipping cabinet with fully assembled polycarbonate sneeze guard

ETL-S listed to NSF standards for use in commercial settings

Choice of gelato pan holders, tub holders, or novelty baskets

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Polycarbonate sneeze guard	Durable sneeze guard with stainless steel support
Fluorescent light	Fully illuminates products for a tempting display
Digital thermostat	Set precise serving temperature with easy electronic controls; temperature range between 0° and 20°F for sorbet service
Caster wheels	Heavy duty casters for smooth mobility
Manual defrost	Front located drain for easy defrosting
Factory installed lock	Keyed lock for secure interior
Hammered aluminum interior	21" deep for maximum storage
Choice of storage accessories	Choose 2 gelato pan holders or 3 tub holders



SCF1076PDC Specifications:

Overview	
Height of Cabinet	48.5" (123 cm)
Width	42.63" (108 cm)
Depth	27.0" (69 cm)
Capacity	10.6 cu.ft. (300 L)
Defrost Type	Manual
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Sanitation	ETL-S
Amps	3.3
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	Sliding
Interior Height	25.63" (65 cm)
Interior Width	37.13" (94 cm)
Interior Depth	20.88" (53 cm)
Thermostat Type	Digital
Interior Light	Yes
Refrigerant Type	R134a
Refrigerant Amount	4.9 oz.
High Side PSI	250.0
Low Side PSI	88.0
Wheels	4
Compressor Step Height	10.5" (27 cm)
Compressor Step Width	12.25" (31 cm)
Temperature Range	0 to 20° F

