



SCFF51OSSSTB



34" x 23.63" x 23.5" (H x W x D)

Frost-free outdoor all-freezer w/digital thermostat, LED light, black cabinet, lock, stainless steel door and towel bar handle; built-in or freestanding

Highlights:

- Weatherproof construction for use in the outdoors
- True frost-free operation saves you maintenance by preventing icy buildup
- Flexible design allows built-in or freestanding use in 24" wide spaces

Product Features:

U.L. approved for outdoor use	Weatherproof design rated safe for outdoor operation
Frost-free operation	No-frost convenience eliminates the need to manually defrost the unit
Stainless steel wrapped door	304 grade stainless steel door stands up to the elements in style
Built-in capable	Make the best use of space by installing your freezer under the counter and flush with other cabinets
Fully finished cabinet	Allows the freezer to be used as a freestanding model
Digital thermostat	Electronic controls offer easy and intuitive temperature management
Factory installed lock	Keyed lock for a secure interior
Recessed LED light	Elegant lighting with an on/off switch located on the control panel
Adjustable shelves	Rearrange your freezer space to accommodate all shapes and sizes or remove shelves for a simple clean-up



SCFF51OSSSTB Specifications:

Overview	
Height of Cabinet	34.0" (86 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.35" (64 cm)
Depth with door at 90°	45.63" (116 cm)
Capacity	4.72 cu.ft. (134 L)
Defrost Type	Frost-Free
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	410.0kWh/year
Amps	2.0
Voltage/Frequency	115 V AC/60 Hz
Weight	108.0 lbs. (49 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101029801
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Chrome
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Digital
Interior Light	Yes
Fan Type	Interior and Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.8 oz.
High Side PSI	270.0
Low Side PSI	106.0

