accuc@ld

SCR450LBI7MED



33.13" x 19.94" x 22.25" (H x W x D)

DISCONTINUED: Replaced by SCR450LBI7MEDDT

Highlights:

Flexible design allows built-in or freestanding use in 20" wide spaces

Factory installed lock provides security you can count on

Commercially listed to NSF-7 standards

Product Features:

Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Commercially listed	ETL-S listed to NSF standards for commercial use
Built-in capable	Make the best use of space by installing your appliance under the counter
Fully finished white cabinet	Allows the unit to be used freestanding
Glass door	Provides a full display of stored contents
Factory installed lock	Keyed lock for secure interior
Automatic defrost	Reduced maintenance with auto defrost system
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Internal fan with heat sink SUMMIT APPLIANCE DIVISION, FELIX STOR	Fan-forced cooling ensures the unit is evenly cooled from top to bottom CH, INC. ISO 9001:2015 Certified

accuc@ld

SCR450LBI7MED Specifications:

Overview		
Height of Cabinet	32.63" (83 cm)	
Height to Hinge Cap	33.13" (84 cm)	
Width	19.94" (51 cm)	
Depth	22.25" (57 cm)	
Capacity	4.1 cu.ft. (116 L)	
Defrost Type	Automatic	
Door	Glass	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	60.0 lbs. (27 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101033334	
Refrigerator Features		
Door Swing	RHD	
Reversible	Factory Reversible	
Height Adjustable	1	
Shelf Type	Wire	
Shelf Qty	3	
Adjustable Shelves	Yes	
Thermostat Type	Dial	
Fan Type	Interior and Exterior	
Refrigerant Type	R134a	
Refrigerant Amount	1.75oz.	
High Side PSI	205.0	
Low Side PSI	103.0	
Level Legs Qty	2	
Wheel Qty	2	
Interior Light	Yes	
Dimensions		
Diffictions		
Interior Height	29.0" (74 cm)	
	29.0" (74 cm) 17.0" (43 cm)	



