



BIM24SS



25" x 15" x 17.75" (H x W x D)

Compact icemaker with manual defrost for undercounter use

Highlights:

- Compact size for easy placement
- Flexible design allows built-in or freestanding use
- Professional exterior for modern look

Product Features:

Reversible door	Keep your options flexible with a reversible door that's easy to switch when your arrangement changes
Manual defrost	Requires defrosting when ice gets too thick
Professional handle	Reversible chrome handle
Built-in capable	Make the best use of space by installing your icemaker under the counter and flush with other cabinets
Fully finished cabinet	Allows the icemaker to be used freestanding
Insulated storage bin	Ice stays solid longer in this cold-protected bin
100% CFC free	Environmentally friendly design without ozone-damaging chemicals



BIM24SS Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	25.0" (64 cm)
Width	15.0" (38 cm)
Depth	17.75" (45 cm)
Depth with Handle	20.0" (51 cm)
Depth with door at 90°	31.38" (80 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	66.0 lbs. (30 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101021263
Icemaker	
Door Swing	RHD
Reversible	Yes
Daily Ice Production	10.0 lbs. (5 kg)
Ice Storage Capacity	10.0 lbs. (5 kg)
Ice Shape	Crescent
Number of Ice Cube Sizes	1
Refrigerant Type	R134a
Refrigerant Amount	2.4 oz.
Interior Height	11.75" (30 cm)
Interior Width	10.0" (25 cm)
Interior Depth	13.0" (33 cm)
Level Legs	2

