



SCR600BLBIPUB



33.5" x 23.63" x 23.5" (H x W x D)

Commercially approved built-in undercounter craft beer Pub Cellar with digital thermostat, glass door, and black cabinet

Highlights:

UNAVAILABLE AT THIS TIME

Commercially approved for use in foodservice establishments

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

Designed for craft beer storage	Wide range temperature control lets you manage the interior between 41° and 65°F for optimum storage of all types of beer
Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Slim undercounter dimensions	Less than 24 inches wide to fit tight spaces
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets
Double pane tempered glass door	Heat resistant design provides clear view to promote impulse buys
Factory installed lock	Keyed lock for a secure interior
Digital thermostat	Exterior thermostat located in kickplate lets you manage the temperature without opening the door
Automatic defrost	Reduced user maintenance with automatic defrost
Adjustable glass shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up

SCR600BLBIPUB Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.5" (65 cm)
Depth with door at 90°	46.0" (117 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101001128
Wine Cellar	
Number of Zones	1
Door Swing	RHD
Reversible	Yes
Adjustable Shelves	Yes
Shelf Type	Glass
Shelf Qty	4
Thermostat Type	Digital
Interior Light	Yes
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	1.8 oz.
High Side PSI	285.0
Low Side PSI	70.0
Interior Height 1	26.0" (66 cm)
Interior Width 1	20.75" (53 cm)
Interior Depth 1	17.5" (44 cm)
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	20.75" (53 cm)
Compressor Step Depth	5.0" (13 cm)
Level Legs	4
Temperature Range	41 to 65°F

