

## **SCR600BLBITB**



34.5" x 23.63" x 24" (H x W x D)

Commercially listed built-in undercounter beverage center in 24" footprint, with black cabinet, glass door, towel bar handle, and lock

## **Highlights:**

UNAVAILABLE AT THIS TIME

Includes adjustable glass shelves for flexible storage

Commercially approved for use in foodservice establishments

## **Product Features:**

Commercially approved	ETL-S Approved to ANSI-NSF Standard 7 and CalCode Compliant	
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinets	
Fully finished black cabinet	Allows the unit to be used freestanding	
Double pane tempered glass door	Heat resistant design provides clear view to promote impulse buys	
Factory installed lock	Keyed lock for a secure interior	
Professional towel bar handle	A curved stainless steel handle provides generous room for a comfortable grip	
Automatic defrost	Reduced user maintenance with automatic defrost	
Adjustable glass shelves	Rearrange your refrigerator space to accommodate all shapes and sizes or remove shelves for a simple clean-up	
One piece interior liner	Enjoy easy clean-up with a seamless liner that won't hold a mess in hidden crevices	







## **SCR600BLBITB Specifications:**

Height of Cabinet         33.5" (85 cm)           Height to Hinge Cap         34.5" (88 cm)           Width         23.63" (60 cm)           Depth         24.0" (61 cm)           Depth with Handle         25.5" (65 cm)           Depth with door at 90°         46.0" (117 cm)           Capacity         5.5 cu.ft. (156 L)           Defrost Type         Automatic           Door         Glass           Cabinet         Black           US Electrical Safety         UL           Canadian Electrical Safety         ULC           Safety         US           Sanitation         ETL-S           Amps         1.0           Voltage/Frequency         115 V AC/60 Hz           Parts & Labor Warranty         1 Year			
Width 23.63" (60 cm)  Depth 24.0" (61 cm)  Depth with Handle 25.5" (65 cm)  Depth with door at 90° 46.0" (117 cm)  Capacity 5.5 cu.ft. (156 L)  Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety ULC  Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Depth 24.0" (61 cm)  Depth with Handle 25.5" (65 cm)  Depth with door at 90° 46.0" (117 cm)  Capacity 5.5 cu.ft. (156 L)  Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Depth with Handle 25.5" (65 cm)  Depth with door at 90° 46.0" (117 cm)  Capacity 5.5 cu.ft. (156 L)  Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Depth with door at 90° 46.0" (117 cm)  Capacity 5.5 cu.ft. (156 L)  Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Capacity 5.5 cu.ft. (156 L)  Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Defrost Type Automatic  Door Glass  Cabinet Black  US Electrical Safety UL  Canadian Electrical Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Door Glass Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Cabinet Black US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
US Electrical Safety  Canadian Electrical Safety  Sanitation  ETL-S  Amps  1.0  Voltage/Frequency  115 V AC/60 Hz			
Canadian Electrical Safety  Sanitation ETL-S  Amps 1.0  Voltage/Frequency 115 V AC/60 Hz			
Safety Sanitation ETL-S Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Voltage/Frequency 115 V AC/60 Hz			
Parts & Labor Warranty 1 Year			
Compressor Warranty 5 Years			
UPC 761101004792			
Refrigerator Features			
Door Swing RHD			
Reversible Factory Reversible			
Height Adjustable 1			
Shelf Type Glass			
Shelf Qty 4			
Adjustable Shelves Yes			
<u> </u>			
Adjustable Shelves Yes			
Adjustable Shelves Yes Thermostat Type Dial			
Adjustable Shelves Yes Thermostat Type Dial Fan Type Exterior			
Adjustable Shelves Yes Thermostat Type Dial Fan Type Exterior Refrigerant Type R134a			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 1.8oz.			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type Refrigerant Amount High Side PSI Dial 285.0			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Thermostat Type Exterior 1.80z. 285.0			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 1.8oz. High Side PSI 285.0 Low Side PSI To.0 Level Legs Qty 4			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type R134a Refrigerant Amount 1.8oz. High Side PSI 285.0 Low Side PSI 70.0 Level Legs Qty 4 Interior Light Yes			
Adjustable Shelves Thermostat Type Dial Fan Type Exterior Refrigerant Type Refrigerant Amount 1.8oz. High Side PSI 285.0 Low Side PSI 70.0 Level Legs Qty 4 Interior Light Yes Dimensions			

Compressor Step Height	6.0" (15 cm)
Compressor Step Width	20.75" (53 cm)
Compressor Step Depth	5.0" (13 cm)



