

VT217



35" x 44.3" x 24" (H x W x D)

DISCONTINUED: Replaced by EL21LT

Highlights:

- Capable of operating at -40° C
- Digital thermostat for the most precision in temperature management
- Corner protectors for exterior safety

Product Features:

-40° C (-40° F) operation	Capable of operating at extra low temperature for safe storage of vaccines, pharmaceuticals, and frozen foods
Digital thermostat	Precise temperature management with easy electronic controls
Alarm	Audible alarm sounds to warn of temperature variations
Front-mounted lock	Lock on handle for trusted security with easy convenience
Commercially approved	UL-S Listed for use in foodservice establishments
Counterbalanced hinges	Allows the lid to remain opened when lifted to 90°
Manual defrost	Stable interior temperature with manual defrost operation
Superior insulation	4" walls for added protection and cold stability inside
Casters	Heavy duty rollers allow smooth mobility

VT217 Specifications:

Overview	
Height of Cabinet	35.0" (89 cm)
Width	44.3" (113 cm)
Depth	24.0" (61 cm)
Depth with Handle	27.4" (70 cm)
Capacity	7.3 cu.ft. (207 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Amps	3.6
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101007496
Freezer	
Door Swing	Lift-up
Interior Height	24.5" (62 cm)
Interior Width	36.25" (92 cm)
Interior Depth	15.63" (40 cm)
Shelf Type	Wire
Thermostat Type	Digital
Interior Light	Yes
Refrigerant Type	R404a
Refrigerant Amount	6.17 oz.
High Side PSI	340.0
Low Side PSI	140.0
Level Legs	2
Compressor Step Height	10.0" (25 cm)
Compressor Step Width	7.75" (20 cm)
Compressor Step Depth	15.63" (40 cm)

