

VT65M7BIFR



33.25" x 23.63" x 23.5" (H x W x D)

Commercial built-in medical all-freezer capable of -25° C operation; stainless steel door frame accepts custom panels

Highlights:

- Flexible design allows built-in or freestanding use
- Insert a custom panel into the two-piece stainless steel door frame to match the unit to other cabinetry
- 25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry
Fully finished white cabinet	Allows the unit to be used freestanding
Stainless steel door frame	Slide a panel into this two-piece U-shaped frame to match your unit to other cabinets (panel size: 23" W x 28" H)
Professional handle	Stainless steel handle can be reversed with door swing
Reversible door	Keep placement options flexible with a reversible door swing that is easy to switch when your arrangement changes
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
Manual defrost	Static and stable cooling with no internal fans
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened

VT65M7BIFR Specifications:

Overview	
Height of Cabinet	33.25" (84 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101042824
Freezer	
Door Swing	RHD
Reversible	Yes
Height Adjustable	1
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)

Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

