accuc@ld

VT65M7BIFRADA



32.25" x 23.63" x 23.5" (H x W x D)

Commercial ADA compliant built-in medical all-freezer capable of -25° C operation, with stainless steel door frame that accepts custom panels

Highlights:

32 inch height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use

Insert a custom panel into the two-piece stainless steel door frame to match the unit to other cabinetry

Product Features:

2 inch height is designed to fit under ADA compliant counters
Make the best use of space by installing your appliance under the counter and flush with ther cabinetry
allows the unit to be used freestanding
Blide a panel into this two-piece U-shaped frame to match your unit to other cabinets (panel ize: 23" W x 28" H)
Stainless steel handle can be reversed with door swing
Keep placement options flexible with a reversible door swing that is easy to switch when your trangement changes
ow temperature operation is ideal for vaccine, pharmaceuticals, and other temperature ensitive materials
Static cooling system for improved temperature stability
) i

accuc@ld

VT65M7BIFRADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	45.63" (116 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101042831
Freezer	
Door Swing	RHD
Reversible	Yes
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)

Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C

