accuc@ld

VT65M7BISSHHADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant commercial built-in medical all-freezer capable of -25° C operation, with wrapped stainless steel door and horizontal handle

Highlights:

32 inch height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
ADA Compliant	32 inch height is designed to fit under ADA compliant counters	
Built-in capable	Make the best use of space by installing your appliance under the counter and flush with other cabinetry	
Fully finished white cabinet	Allows the unit to be used freestanding	
Stainless steel door	Durable design with lasting elegance	
Professional horizontal handle	Thin 14mm diameter on stainless steel handle, mounted horizontally across the door	
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials	
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened	
Manual defrost	Static cooling system for improved temperature stability	



accuc@ld

VT65M7BISSHHADA Specifications:

Height of Cabinet 32.0" (81 cm) Height to Hinge Cap 32.25" (82 cm) Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 25.13" (64 cm) Depth with door at 90° 46.0" (117 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manua Door Stainless Stee Cabinet White US Electrical Safety ULC Sanitation ETL-S Amps 12.69			
Width 23.63" (60 cm) Depth 23.5" (60 cm) Depth with Handle 25.13" (64 cm) Depth with door at 90° 46.0" (117 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manua Door Stainless Stee Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
Depth with Handle 25.13" (60 cm. Depth with Handle 25.13" (64 cm. Depth with door at 90° 46.0" (117 cm. Capacity 3.5 cu.ft. (99 L. Defrost Type Manual Door Stainless Steel Cabinet White US Electrical Safety ULC Safety Sanitation ETL-S			
Depth with Handle 25.13" (64 cm) Depth with door at 90° 46.0" (117 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manua Door Stainless Stee Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
Depth with door at 90° 46.0" (117 cm) Capacity 3.5 cu.ft. (99 L) Defrost Type Manual Door Stainless Stee Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
Capacity 3.5 cu.ft. (99 L) Defrost Type Manua Door Stainless Stee Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
Defrost Type Manual Door Stainless Stee Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
Door Stainless Stee Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation ETL-S			
Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation ETL-S			
US Electrical Safety Canadian Electrical Safety Sanitation ETL-S			
Canadian Electrical ULC Safety Sanitation ETL-S			
Safety Sanitation ETL-S			
Amps 1.3			
Voltage/Frequency 115 V AC/60 Hz			
Weight 105.0 lbs. (48 kg			
Parts & Labor Warranty 1 Yea			
Compressor Warranty 5 Years			
UPC 761101042879			
Freezer			
Door Swing RHD			
Reversible Yes			
Crisper Finish Opaque			
Crisper Cover Glass			
Interior Height 24.25" (62 cm			
Interior Width 17.75" (45 cm)			
Interior Depth 16.5" (42 cm			
Shelf Type Glass			
Thermostat Type Digita			
Thermostat Type Digita Refrigerant Type R134a			
Refrigerant Type R134a			
Refrigerant Type R134a Refrigerant Amount 2.7 oz			
Refrigerant Type R134a Refrigerant Amount 2.7 oz High Side PSI 235.0			
Refrigerant Type R134a Refrigerant Amount 2.7 oz High Side PSI 235.0 Low Side PSI 70.0			
Refrigerant Type R134a Refrigerant Amount 2.7 oz High Side PSI 235.0 Low Side PSI 70.0 Interior Drawers Yes			

Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C



