

# VT65MIFADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant commercially listed medical all-freezer, capable of -25° C operation and accepting full overlay panels on the door

**Highlights:**

- ETL-S listed for commercial use
- 32 inches high to meet ADA guidelines for lower counter height
- Ideal 24 inch footprint fits easily in tight settings

**Product Features:**

ADA Compliant	32 inch height is designed to meet ADA guidelines for lower counter height
Commercially approved	ETL-S Listed and CalCode Compliant
Fully finished white cabinet	Allows the unit to be used freestanding
Integrated door frame	Customize the front by mounting an overlay panel over the door; seamless look can blend into cabinetry with no exposed frame. Handle not included. (panel dimensions: 23 5/16" W x 28 1/4" H)
Reversible door	Keep placement options flexible with a reversible door swing that is easy to switch when your arrangement changes
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials
No internal fans	Static cooling system
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened
Manual defrost	Energy efficient operation

## VT65MIFADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043128
Freezer	
Door Swing	RHD
Reversible	Yes
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C

