accuc@ld

VT65ML7



33.5" x 23.63" x 23.5" (H x W x D)

Commercially listed -25°C medical all-freezer with front lock, for freestanding use

Highlights:

ETL-S listed to NSF-7 commercial standards

Factory-installed lock provides security you can count on

-25° C operation for safe storage of temperature sensitive materials

Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
Fully finished white cabinet	Allows the freezer to be used freestanding	
Slim counter height dimensions	24" footprint allows versatile placement	
Factory installed lock	Keep contents secure with a key lock on the door	
-25° C capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials	
Manual defrost	Static cooling system for improved temperature stability	
Three removable storage baskets	Wire drawers allow for easy storage organization	
Adjustable thermostat	Manage the interior temperature with ease and accuracy	
One piece interior liner	Enjoy easy clean-up with a seamless liner that won't hold a mess in hidden crevices	



accuc@ld

VT65ML7 Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.5" (85 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101043135
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
	70.0
Low Side PSI	
Low Side PSI Level Legs	2
Level Legs	2
Level Legs Interior Drawers	2 Yes

Compressor Step Depth	5.5" (14 cm)
Temperature Range	-12°C to -25°C
Sound Level	33 dB



