# accucold

# VT65ML7BIIF



## 33.5" x 23.63" x 23.5" (H x W x D)

Commercial built-in medical all-freezer capable of -25° C operation with front lock; door accepts full overlay panels

#### **Highlights:**

Flexible design allows built-in or freestanding use

 $\mbox{-}25^{\rm o}$  C operation for safe storage of temperature sensitive materials

Three slide-out freezer drawers help contents maintain stable temperature, even with an open door

### **Product Features:**

Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments	
Fully finished white cabinet	Allows the unit to be used freestanding	
Factory installed lock	Keyed lock for a secure interior	
Integrated door frame	Customize the front by mounting an overlay panel over the door; seamless look can blend into cabinetry with no exposed frame. Handle not included. (panel dimensions: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)	
-25° capable	Low temperature operation is ideal for vaccine, pharmaceuticals, and other temperature sensitive materials	
Manual defrost	Static cooling system for improved temperature stability	
Three slide-out drawers	Conveniently organize your items while keeping the temperature stable when the door is opened	
Adjustable thermostat	Manage the temperature with ease and accuracy	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



# accuceld

## **VT65ML7BIIF Specifications:**

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.5" (85 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.5" (60 cm)
Capacity	3.5 cu.ft. (99 L)
Defrost Type	Manua
Door	Panel-Ready
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Yea
Compressor Warranty	5 Years
UPC	761101043180
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Crisper Finish	Opaque
Crisper Cover	Glass
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Dia
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)

Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.0" (15 cm)
Temperature Range	-12°C to -25°C



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

